









Stock Item Denoted by Shaded Background

400/500 SERIES STAINLESS STEEL (DRY, LIQUID & AMMONIA) GAUGE ACCESSORIES

MODEL NO.	15-401	15-411	25-400	25-410	40-400	40-410	60-400	60-410
			25-500	25-510	40-500	40-510	60-500	60-510
CONNECTION								
304 SS Front Flange (SSFF)	—	—	—					
304 SS Rear Flange (SSRF)	—	—						
SS Bezel w/U-Clamp (SSB-U)	—	—	—	—	—		—	
Installed 304SS Panel Mount Clamp (SPMC)	—	—	—		—	—	—	—
Uninstalled 304SS Panel Mount Clamp (25-459-1-SS-PMC)	—	—	—		—	—	—	—
Installed Steel Panel Mount Clamp (PMC)	—	—	—		—	—	—	—
Uninstalled Steel Panel Mount Clamp (25-459-1-PMC)	—	—	—		—	—	—	—
Flange Ring (FR)	—	—	—		—	—	—	—
Flange Ring 304SS (SSFR)	—	—	—		—	—	—	—
Adjustable Pointer (AP)	—	—	—	—				
Safety Glass Lens (SG)	—	—						
Maximum Indicating Pointer (MIP)	—	—						
Red Set Pointer (SP)	—	—						
Laser Marking (LM)								
Stainless Steel Tagging (ST)								
Orifice - 316SS Threaded 0.8mm (ST8)								
Orifice - 316SS Threaded 0.5mm (ST5)								

STANDARD ORIFICE FOR 400/500 SERIES GAUGE IS 0.8 mm THREADED.

C = Consult Factory for Price and Availability. STD = Standard Stock Model Specification. — = Currently not Available.
Consult Factory for additional Non-Stock and Special Accessory availability.