

ORDERING INFORMATION

TYPES	10 (2,000 psi)	10H (5,000 psi)		
INSTRUMENT CONNECTION SIZES	02 1/4" NPT	04 1/2" NPT		
UPPER HOUSING MATERIALS	C Carbon Steel	S 316 Stainless Steel		
DIAPHRAGM MATERIALS	A Tantalum	M Monel 400	S 316 Stainless Steel **	U Titanium Grade 4
	H Hastelloy C – 276	N Inconel 600	T PTFE *, †	V FKM *, ***
O-RING MATERIALS	B NBR	T PTFE ¹	V FKM	
PROCESS CONNECTION SIZES	02 1/4" NPT	06 3/4" NPT	10 1-1/4" NPT	
	04 1/2" NPT	08 1" NPT	12 1-1/2" NPT	
	(ASME and DIN flanges available upon request)			
LOWER HOUSING MATERIALS	C Carbon Steel	M Monel 400	S 316 Stainless Steel	
	H Hastelloy C-276	N Inconel 600	U Titanium	
FLUSHING CONNECTIONS	1F 1/8" NPT	2F 1/4" NPT		

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* Not available with 10H

** NBR o-rings standard with 316SS diaphragm

*** FKM o-rings standard with FKM diaphragm

† PTFE o-rings standard with all other diaphragms