

ORDERING INFORMATION

TYPE	30 (2,500 psi)	30H (5,000 psi)		
INSTRUMENT CONNECTION SIZES	02 1/4" NPT	04 1/2" NPT		
UPPER HOUSING MATERIALS	C Carbon steel	P Carpenter 20	U Titanium Grade 4	
	M Monel 400	S 316 Stainless steel		
DIAPHRAGM MATERIALS	A Tantalum	M Monel 400 ¹	P Carpenter 20 ¹	U Titanium Grade 4 ¹
	H Hastelloy C-276	N Inconel 600	S 316 Stainless steel	
SEAL GASKET MATERIALS	F FEP encapsulated o-ring (5,000 psi)	T PTFE		
	R Klingersil C-4401 (Rated to 1,500 psi)	V FKM		
PROCESS CONNECTION SIZES	02 1/4" NPT	06 3/4" NPT	10 1-1/4" NPT	
	04 1/2" NPT	08 1" NPT	12 1-1/2" NPT	
	(ASME and DIN Flanges Available Upon Request)			
LOWER HOUSING MATERIALS	C Carbon Steel	M Monel 400	P Carpenter 20	U Titanium Grade 4
	H Hastelloy C-276	N Inconel 600	S 316 Stainless Steel	
FLUSHING CONNECTIONS	1F 1/8" NPT	2F 1/4" NPT		

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

¹ When selecting a Monel 400, Carpenter 20 or Titanium Grade 4 Diaphragm, the upper housing must be the same material