

ORDERING INFORMATION

SERIES	627		
PRESSURE RANGES	50inH ₂ O 0 inH ₂ O to 50 inH ₂ O	5 0 psig to 5 psig (11.5 ftH ₂ O)	100 0 psig to 100 psig (230.7 ftH ₂ O)
	100inH ₂ O 0 inH ₂ O to 100 inH ₂ O	10 0 psig to 10 psig (23.1 ftH ₂ O)	160 0 psig to 160 psig (369.1 ftH ₂ O)
	150inH ₂ O 0 inH ₂ O to 150 inH ₂ O	15 0 psig to 15 psig (34.6 ftH ₂ O)	200 0 psig to 200 psig (461.3 ftH ₂ O)
	250inH ₂ O 0 inH ₂ O to 250 inH ₂ O	25 0 psig to 25 psig (57.7 ftH ₂ O)	300 0 psig to 300 psig (692.3 ftH ₂ O)
	400inH ₂ O 0 inH ₂ O to 400 inH ₂ O	30 0 psig to 30 psig (69.2 ftH ₂ O)	350 0 psig to 350 psig (807.3 ftH ₂ O)
		60 0 psig to 60 psig (138.4 ftH ₂ O)	
	psig = gauge pressure	inH ₂ O = inches of water	ftH ₂ O = feet of water Other ranges available on request.
ACCURACIES	1 ±0.25% full scale (BFSL)	2 ±0.125% full scale (BFSL) on ≥ 150 inH ₂ O	
OUTPUT SIGNAL	1 4 mA to 20 mA, 2-wire		
PROCESS CONNECTIONS	N Stainless steel nosecone	W Stainless steel weighted nosecone (1.1 lb.)	
	T G 1/2 B x 1/2" NPT male with 1/4" NPT female		
ELECTRICAL CONNECTIONS	XX Standard Polyurethane cable		
	38-XX Optional FEP cable	NOTE: XX = length of cable in feet	
OPTIONS	CBC Cable Clamp	FE Filter Element	
	DC Desiccant Cartridge	JB Cable Junction Box	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.