

ORDERING INFORMATION

SERIES	627			
PRESSURE RANGES	50inH ₂ O	0 inH ₂ O to 50 inH ₂ O	5	0 psig to 5 psig (11.5 ftH ₂ O)
	100inH ₂ O	0 inH ₂ O to 100 inH ₂ O	10	0 psig to 10 psig (23.1 ftH ₂ O)
	150inH ₂ O	0 inH ₂ O to 150 inH ₂ O	15	0 psig to 15 psig (34.6 ftH ₂ O)
	250inH ₂ O	0 inH ₂ O to 250 inH ₂ O	25	0 psig to 25 psig (57.7 ftH ₂ O)
	400inH ₂ O	0 inH ₂ O to 400 inH ₂ O	30	0 psig to 30 psig (69.2 ftH ₂ O)
			60	0 psig to 60 psig (138.4 ftH ₂ O)
psig = gauge pressure inH ₂ O = inches of water ftH ₂ O = feet of water Other ranges available on request.				
ACCURACIES	1	±0.25% full scale (BFSL)		
	2	±0.125% full scale (BFSL) on ≥ 150 inH ₂ O		
OUTPUT SIGNAL	1	4 mA to 20 mA, 2-wire		
PROCESS CONNECTIONS	N	Stainless steel nosecone		
	T	NPT adapter, 1/2" NPT male outer thread with 1/4" NPT female inner thread attached to transmitter process connection with straight thread and o-ring seal		
ELECTRICAL CONNECTIONS	XX	Standard Polyurethane cable		
	38-XX	Optional FEP cable		
		NOTE: XX = length of cable in feet		
OPTIONS	CBC	Cable Clamp		
	DC	Desiccant Cartridge		
	FE	Filter Element		
	JB	Cable Junction Box		

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.