

ORDERING INFORMATION

SERIES	500							
SWITCH FUNCTIONS	1	1 N.O. (PNP)	3	2 N.O. (PNP)	5	1 N.O. (NPN)	7	2 N.O. (NPN)
	2	1 N.C. (PNP)	4	2 N.C. (PNP)	6	1 N.C. (NPN)	8	2 N.C. (NPN)
PROCESS CONNECTIONS	1	1/8" NPT male	2	1/4" NPT male				
PRESSURE RANGES	30vac	-30 inHg to 0 psig	150	0 psig to 150 psig	1000	0 psig to 1,000 psig	6000	0 psig to 6,000 psig
	15	0 psig to 15 psig	250	0 psig to 250 psig	1500	0 psig to 1,500 psig	7500	0 psig to 7,500 psig
	30	0 psig to 30 psig	350	0 psig to 350 psig	2000	0 psig to 2,000 psig		
	60	0 psig to 60 psig	600	0 psig to 600 psig	3000	0 psig to 3,000 psig		
	100	0 psig to 100 psig	750	0 psig to 750 psig	5000	0 psig to 5,000 psig		
ELECTRICAL CONNECTIONS	2	M12x1 (4-pin)						
OPTIONS	BT8	Threaded Orifice						
	Note:	M12 mating connectors & cord sets are available as separate options.						

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.