

ORDERING INFORMATION

SERIES	800							
TEMPERATURE RANGES	-40/120	-40 °F to 120 °F	0/200	0 °F to 200 °F	0/300	0 °F to 300 °F	0/750	0 °F to 750 °F
	25/125	25 °F to 125 °F	20/240	20 °F to 240 °F	50/300	50 °F to 300 °F	0/1000	0 °F/ to 1,000 °F
	0/140	0 °F to 140 °F	0/250	0 °F to 250 °F	50/500	50 °F to 500 °F	Custom ranges from -300 °F through 1,100 °F available on request (90 °F / 50 °C minimum span)	
ACCURACY	1 Class B + ($\pm 0.5\%$ BFSL)							
OUTPUT SIGNALS	1	4 mA to 20 mA, 2-wire	3	1 Vdc to 5 Vdc, 3-wire				
	2	0 Vdc to 5 Vdc, 3-wire	5	0 Vdc to 10 Vdc, 3-wire				
PROCESS CONNECTIONS	2	1/4" NPT Male			48	1/2" NPT Male w/adjustable compression fitting		
	8	1/2" NPT Male						
ELECTRICAL CONNECTIONS	1	36" cable (connected to option 8)			14	Hirschmann connection w/ISO 4400 1/2 "NPT conduit		
	8	Hirschmann (DIN EN 175301-803 Form A)			25	M12 x 1 (4-pin)		
STEM LENGTHS	025	2.5"			060	6"	120	12"
	040	4"			090	9"		
STEM DIAMETERS	3	Tapered from 6 mm - 3 mm tip			6	6 mm	8	8 mm

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.