

ORDERING INFORMATION

SERIES	850					
SWITCH FUNCTIONS	1	2 N.O. or 2 N.C. switch (PNP*)		4	2 N.O. or 2 N.C. switch (PNP*) with 4 mA to 20 mA 3-wire analog output**	
	2	1 N.O. or 1 N.C. switch (PNP*) with 4 mA to 20 mA 3-wire analog output		5	2 N.O. or 2 N.C. switch (PNP*) with 0 Vdc to 10 Vdc 3-wire output)**	
	3	1 N.O. or 1 N.C. switch (PNP*) with 0 Vdc to 10 Vdc 3-wire output				
PROCESS CONNECTIONS	2	1/4" NPT Male		47	1/4" NPT Male sliding compression fitting	
	8	1/2" NPT Male		48	1/2" NPT Male sliding compression fitting	
TEMPERATURE RANGES	-4/176	-4 °F to 176 °F (-20 °C to 80 °C)		-4/248	-4 °F to 248 °F (-20 °C to 120 °C) †	
ELECTRICAL CONNECTION	2	M12 x 1 (4-pin)		3	M12 x 1 (5-pin, 2 switch and output)	
STEM LENGTHS	25mm	25 millimeters***		100mm	100 millimeters	250mm 250 millimeters
	50mm	50 millimeters***		150mm	150 millimeters	350mm 350 millimeters
STEM DIAMETERS	6	6 mm				

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* NPN available, consult factory

** Available only with M12 x 1 (5-pin) connector

*** Not available with sliding compression fitting

† Available only with sliding compression fitting process connection and stem lengths ≥100 mm