

ORDERING INFORMATION

SERIES	900		
TEMPERATURE RANGES	-50/400 -50/750	-50 °F to 400 °F -50 °F to 750 °F	-330/1100 -330 °F to 1,100 °F
ACCURACIES	1	±0.12% (±0.3 °C) at 0 °C, Class B	3 ±0.04% (±0.1 °C) at 0 °C, Class AA
	2	±0.06% (±0.15 °C) at 0 °C, Class A	
ELEMENT TYPES	C	PT100 Ω at 0 °C	M PT1000 Ω at 0 °C
CIRCUIT TYPES	1	Single, 2-wire	3 Single, 4-wire 5 Dual, 3-wire
	2	Single, 3-wire	4 Dual, 2-wire 6 Dual, 4-wire
PROCESS CONNECTIONS	0	None	8 1/2" NPT Male
	1	1/8" NPT Male	48 1/2" NPT Male w/ adjustable compression fitting
	2	1/4" NPT Male	
ELECTRICAL CONNECTIONS	6	1/2" NPT conduit with 36" cable	48 M12 x 1 (5-pin)*
	36	Integral cable 36"	49 3-pin RTD plug
	37	1/2" NPT conduit with 6" flying leads	50 M12 x 1 (8-pin)
STEM LENGTHS	025	2.5"	090 9" 180 18"
	040	4"	120 12" 240 24"
	060	6"	150 15"
STEM DIAMETERS	1	1/8"	3 3/8" 6 6 mm
	2	1/4"	4 1/2"

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* Single circuit types only