

ORDERING INFORMATION

SERIES	910 Fixed RTD	915 Spring-loaded RTD
TEMPERATURE RANGES	-50/400 -50 °F to 400 °F -50/750 -50 °F to 750 °F	-330/1100 -330 °F to 1,100 °F
ACCURACIES	1 ±0.12% (±0.3 °C) at 0 °C, Class B 2 ±0.06% (±0.15 °C) at 0 °C, Class A	3 ±0.04% (±0.1 °C) at 0 °C, Class AA
ELEMENT TYPES	C PT100 Ω at 0 °C	M PT1000 Ω at 0 °C
CIRCUIT TYPES	1 Single, 2-wire 2 Single, 3-wire	3 Single, 4-wire 4 Dual, 2-wire 5 Dual, 3-wire 6 Dual, 4-wire
OPTIONAL TRANSMITTER/ OUTPUT	1U 4 mA to 20 mA, 2-wire, upscale burnout 1D 4 mA to 20 mA, 2-wire, downscale burnout 2 0 Vdc to 5 Vdc, 3-wire	3 1 Vdc to 5 Vdc, 3-wire 5 0 Vdc to 10 Vdc, 3-wire
PROCESS CONNECTIONS	0 None 2 1/4" NPT Male	8 1/2" NPT Male
ELECTRICAL CONNECTIONS	23 Connection head w/ 1/2" NPT conduit	45 Connection head with 3/4" NPT conduit
ELECTRICAL CONNECTION MATERIALS	A1 Aluminum cast A2 Aluminum cast, explosion proof*	P1 PP, white S1 Stainless steel cast S2 Stainless steel cast, explosion proof*
STEM LENGTHS	025 2.5" 040 4" 060 6"	090 9" 120 12" 150 15" 180 18" 240 24"
STEM DIAMETERS	1 1/8" 2 1/4"	3 3/8" 4 1/2" 6 6 mm

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* Factory Mutual and Canadian Standards approved explosion proof Class I, Division I, Groups B, C and D; Class II, Division I, Groups E, F and G