

## ORDERING INFORMATION

SERIES	800	Stainless steel housing	810	Black anodized aluminum housing
SWITCH FUNCTIONS	1	2 N.O. or N.C. (PNP or NPN)	3	1 N.O. or 1 N.C. (PNP or NPN) with 0 Vdc to 10 Vdc analog output
	2	1 N.O. or 1 N.C. (PNP or NPN) with 4 mA to 20 mA analog output	4	2 N.O. or 2 N.C. (NPN) with 4 mA to 20 mA analog output*
PROCESS CONNECTIONS	2	1/4" NPT male	10	G 1/4 B male
	8	1/2" NPT male	11	G 1/2 B male
ADJUSTABLE RANGES † <i>(Max. working pressure)</i>	14.5/75	-14.5 psig to 75 psig	145	0 psig to 145 psig
	14.5/145	-14.5 psig to 145 psig	300	0 psig to 300 psig
	75	0 psig to 75 psig	750	0 psig to 750 psig
ELECTRICAL CONNECTIONS	1450	0 psig to 1,450 psig	6000	0 psig to 6,000 psig
	2400	0 psig to 2,400 psig	9000	0 psig to 9,000 psig
	3750	0 psig to 3,750 psig	10000	0 psig to 10,000 psig
ELECTRICAL CONNECTIONS	2	M12 x 1 (4-pin)	3	M12 x 1 (5-pin), 2 switch and analog output
	45	SAE J1926-3:7/16-20		
OPTIONS	ST8	Threaded Orifice	RB	Rotatable Base
			EH	Enhanced Software**
			PC	Protective Cover (IP67)

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

\* Available only with a M12 x 1 (5-pin) connector. Rotatable base is not available on this option.

\*\* Includes minimum/maximum value memory, output dampening, switching time delay

† Please specify switch set point(s), rising or falling pressing, and switch hysteresis (if applicable)