

ORDERING INFORMATION

SERIES	800 Stainless steel housing					
SWITCH FUNCTIONS	1	2 N.O. or N.C. (PNP or NPN)			3	1 N.O. or 1 N.C. (PNP or NPN) with 0 Vdc to 10 Vdc analog output
	2	1 N.O. or 1 N.C. (PNP or NPN) with 4 mA to 20 mA analog output			4	2 N.O. or 2 N.C. (NPN) with 4 mA to 20 mA analog output*
PROCESS CONNECTIONS	2	1/4" NPT male	10	G 1/4 B male	45 SAE J1926-3:7/16-20	
	8	1/2" NPT male	11	G 1/2 B male		
ADJUSTABLE RANGES † (Max. working pressure)	14.5/75	-14.5 psig to 75 psig		145	0 psig to 145 psig	
	14.5/145	-14.5 psig to 145 psig		300	0 psig to 300 psig	
	75	0 psig to 75 psig		750	0 psig to 750 psig	
ELECTRICAL CONNECTIONS	2	M12 x 1 (4-pin)			3 M12 x 1 (5-pin), 2 switch and analog output	
	ST8	Threaded Orifice		RB	Rotatable Base	
OPTIONS				EH	Enhanced Software**	
				PC	Protective Cover (IP67)	

Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

* Available only with a M12 x 1 (5-pin) connector. Rotatable base is not available on this option.

** Includes minimum/maximum value memory, output dampening, switching time delay

† Please specify switch set point(s), rising or falling pressing, and switch hysteresis (if applicable)