



500 SERIES

- Vacuum ranges through 0 psig to 10,000 psig
- Standard copper alloy wetted parts
- Normally open (N.O.) or normally closed (N.C.) switching functions
- CE compliant to suppress RFI, EMI and ESD

APPLICATIONS

- HVAC
- Hydraulics & pneumatics
- Pumps and compressors
- Stamping & forming presses
- Transportation

SPECIFICATIONS

Switching parameters	
Number	1 or 2
Function	N.O. or N.C., p-switching
Contact rating	Max. 100 mA (max. 30 Vdc)
Non-repeatability	≤ 1% of full scale
Pressure ranges	
Vacuum ranges through 0 psig to 10,000 psig	
Switch adjustment	
Switch point	Adjustment screw Switching point 5 ...100% of full scale
Hysteresis	≤ 5% of full scale
Service life	
>1,000,000 load cycles	
Temperature ranges	
Compensated 32° to 175 °F / 0° to 80 °C	
Zero ± 0.06% full scale/ °F	
Span ± 0.06% full scale/ °F	
Media -5° to 175 °F (-20° to 80 °C)	
Ambient -5° to 175 °F (-20° to 80 °C)	
Storage -22° to 175 °F (-30° to 80 °C)	
Power requirement*	
10 Vdc to 30 Vdc	
Proof pressure	
30 psi & lower	5x
60 psi	4x
150 psi & higher	2x
Measuring element	
Copper alloy	
316 SS > 600 psi	
1/4" NPT Brass connection standard	
Housing material	
Brass through 350 psi	
Aluminum anodized 600 psi and higher	
Environmental rating	
IP67 for M12 x 1	
Electromagnetic rating	
CE compliant to EMC norm EN 61326:1997/A1:1998	
RFI, EMI and ESD protection	
Weight	
0.2 lb. on ≤400 psi, 0.6 lb. on ≥600 psi	

* Unregulated



ORDERING INFORMATION				
SERIES	500			
SWITCH FUNCTIONS	1 1 N.O. (PNP)	2 1 N.C. (PNP)	3 2 N.O. (PNP)	4 2 N.C. (PNP)
PROCESS CONNECTIONS	1 1/8" NPT male	2 1/4" NPT male		
PRESSURE RANGES	30vac -30 inHg to 0 psig	100 0 psig to 100 psig	750 0 psig to 750 psig	5000 0 psig to 5,000 psig
	15 0 psig to 15 psig	150 0 psig to 150 psig	1000 0 psig to 1,000 psig	7500 0 psig to 7,500 psig
	30 0 psig to 30 psig	250 0 psig to 250 psig	2000 0 psig to 2,000 psig	
	60 0 psig to 60 psig	350 0 psig to 350 psig	3000 0 psig to 3,000 psig	
ELECTRICAL CONNECTIONS	2 M12x1 (4-pin)			
OPTIONS	BT8 Threaded Orifice			
	Note: M12 mating connectors & cord sets are available as separate options.			


Please consult your local NOSHOK Distributor or NOSHOK, Inc. for availability and delivery information.

EXAMPLE

500 - 3 - 2 - 750 - 2 - BT8

Series 500 Series
 Switch function..... 2 N.O. (PNP)
 Process connection 1/4" NPT Male
 Adjustable range 0 psig to 750 psig
 Electrical connection M12 x 1 (4-pin)
 Option..... Threaded Orifice


Additional
Ordering
Information
Switch Set
Point(s)
(please specify)




400 psi & lower

600 psi & higher

Switching Output Schematic



Wiring Diagrams



Connection table for M12x1 (4-pin) connector

Function	Connector M12 x 1 (4-pin)
Power supply: +	1
Power supply: -	3
Switching output: S1	4
Switching output: S2	2